

## SAFETY DATA SHEET

### Section 1 - Product and Company Identification

**Product:** Amazing Mold Rubber Base A Side  
**CAS #:** Non-Applicable  
**Product Use:** Mold Making and Casting  
**Manufacturer/Supplier:**  
**Company Name:** Alumilite  
**Company Address:** 315 E. North St.  
Kalamazoo, MI 49007

**Emergency Telephone Number:** Chemtrec 1-800-424-9300

### Section 2 - Hazards Identification

#### 2.1 GHS Classification

<i>Health</i> Not Classified	<i>Environmental</i> Not Classified	<i>Physical</i> Not Classified
---------------------------------	--	-----------------------------------

#### 2.2 GHS Signal Word, Hazard Statement, Symbol

<b>Pictograms by CLP/GHS:</b>	<b>Not Required</b>
<b>Pictograms by DPD:</b>	<b>Not Required</b>
<b>Signal Word:</b>	<b>Not Required</b>

#### *Hazard Statements*

Causes mild skin irritation and mild eye irritation.

#### *Precautionary statements*

Wear appropriate gloves, protective spectacles, and the protection side.  
Wash hands well after handling.  
Avoid discharge into the environment.

### Section 3 - Composition / Information on Ingredients

	CAS No.	Percentage
Silicone Base	N/A	100%

### Section 4 – First Aid

**Eye Contact:** Flush with large amounts of clean water for 15 minutes. If irritation persists, get medical attention.  
**Skin Contact:** No first aid should be needed.  
**Inhalation:** No first aid should be needed  
**Ingestion:** No first aid should be needed  
**Comments:** Treat symptomatically.

## SAFETY DATA SHEET

### Section 5 – Fire Fighting Measures

---

<b>Extinguishing Media:</b>	On large fires use dry chemical, foam, or water spray. On small fires use carbon dioxide (CO <sub>2</sub> ), dry chemical, or water spray. Water can be used to cool fire-exposed containers.
<b>Fire Fighting Instructions:</b>	Firefighters should be equipped with self-contained breathing apparatus and protective clothing. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.
<b>Flash Point:</b>	>480 °F
<b>Autoignition Temp:</b>	N/A

### Section 6 – Accidental Release Measures

---

<b>General:</b>	For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Clean area as appropriate since some silicone materials, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents, or detergents. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur.
<b>Waste Disposal:</b>	Dispose in accordance with local, state and federal laws and regulations.

### Section 7 – Handling and Storage

---

<b>General:</b>	Use with adequate ventilation. Product evolves n-propyl alcohol when exposed to water or humid air. Provide ventilation during use to control n-propyl alcohol within exposure guidelines or use respiratory protection. Avoid eye contact.
<b>Storage:</b>	Store away from oxidizing materials.

### Section 8 – Exposure Controls & Personal Protection

---

<b>Clothing:</b>	Gloves, coveralls, apron, boots as necessary to prevent skin contact.
<b>Eyes:</b>	Chemical goggles.
<b>Respiration:</b>	Should not be needed.
<b>Ventilation:</b>	General ventilation.

### Section 9 – Physical & Chemical Properties

---

<b>Color:</b>	White
<b>Form:</b>	Viscous Liquid
<b>Odor:</b>	Slight odor
<b>Odor Intensity:</b>	Slight
<b>Specific Gravity:</b>	1.2 (at 25 °C)
<b>Boiling Point:</b>	N/A
<b>Viscosity:</b>	20,000 cps
<b>Solubility:</b>	N/A

## SAFETY DATA SHEET

### Section 10 – Stability & Reactivity

<b>Stability:</b>	Stable
<b>Conditions to Avoid:</b>	None
<b>Incompatibility:</b>	Oxidizing material can cause a reaction.
<b>Hazardous Polymerization:</b>	Will not occur.
<b>Hazardous Decomposition:</b>	Carbon oxides, carbon compounds, silicon dioxide, metal oxides, quartz, & formaldehyde.

### Section 11 – Toxicological Information

No applicable data for this section

### Section 12 – Ecological Information (Non Mandatory)

#### Ecotoxicity Classification Criteria

Hazard Parameters (LC50 or EC50):	High	Medium	Low
Acute Aquatic Toxicity (mg/L)	<=1	>1 and <=100	>100
Acute Terrestrial Toxicity	<=100	>100 and <=2000	>2000

### Section 13 – Disposal Information (Non Mandatory)

**Waste Disposal:** Dispose in accordance with local, state and federal laws and regulations

### Section 14 – Transportation Information (Non Mandatory)

Not regulated by the Department of Transportation.

### Section 15 – Regulatory Information (Non Mandatory)

**Section 313 Toxic Chemicals:** No applicable data for this section.

**Hazardous Health Rating:** Health: 0 Fire: 1 Reactivity: 0

### Section 16 – Other Information

No data available

The information contained in this Safety Data Sheet is to the best of Alumilite's knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. **NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE CONCERNING THE INFORMATION HEREIN PROVIDED OR ANY RELATED PRODUCT.** User is responsible for determining whether the Alumilite product is fit for user's particular purpose and suitable for user's use or application. Given the variety of factors that can affect the use and application of an Alumilite product, it is the user's obligation to determine the suitability of the product for its intended application, and user assumes all risk and liability for safe use of the product. Alumilite's liability is limited to product replacement only after review/testing of product alleged to be defective that is returned to Alumilite in accordance with Alumilite's Shipping and Returns Policy. In no event shall Alumilite be liable for punitive, consequential or indirect damages or damages in excess of the purchase price of the product.

Revised May 2, 2018

## SAFETY DATA SHEET

### Section 1 - Product and Company Identification

**Product:** Amazing Mold Rubber Catalyst B Side  
**CAS #:** Non-Applicable  
**Product Use:** Mold Making and Casting  
**Manufacturer/Supplier:**  
**Company Name:** Alumilite  
**Company Address:** 315 E. North St.  
Kalamazoo, MI 49007

**Emergency Telephone Number:** Chemtrec 1-800-424-9300

### Section 2 - Hazards Identification

#### 2.1 GHS Classification

*Health*  
Not Classified

*Environmental*  
Not Classified

*Physical*  
Not Classified

#### 2.2 GHS Signal Word, Hazard Statement, Symbol

**Pictograms by CLP/GHS:**



**Signal Word:** Danger

#### *Hazard Statements*

Causes skin burns, causes eye irritation.  
May cause respiratory irritation.

#### *Precautionary statements*

Avoid contact with the skin, eyes, and clothing.  
Wear appropriate gloves, protective spectacles, and the protection side.  
Wash hands well after handling.  
Avoid discharge into the environment

### Section 3 - Composition - Information on Ingredients:

	CAS No.	Percentage
Dibutyltin Dilaurate	77-58-7	3-8%
Tetraethoxysilane	78-10-4	15-25%
Maleic Anhydride	108-31-6	<2%

## SAFETY DATA SHEET

### Section 4 – First Aid

---

#### First Aid Procedures

<b>Eye Contact:</b>	Flush with large amounts of clean water for 15 minutes. If irritation persists, get medical attention.
<b>Skin Contact:</b>	Wash with soap and water. Get medical attention if irritation develops or persists. Wash clothing before use.
<b>Inhalation:</b>	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen and continue to monitor. Get immediate medical attention.
<b>Ingestion:</b>	Do not induce vomiting! Do not give liquids! Get medical attention immediately. Remove stomach content by gastric suction only as directed by medical personnel.

### Section 5 – Fire Fighting Measures

---

<b>Extinguishing Media:</b>	Water spray, foam, carbon dioxide, or dry chemical.
<b>Fire Fighting Instructions:</b>	Firefighters should be equipped with self-contained breathing apparatus and turn out gear. Use water spray to cool fire exposed surfaces and to protect personnel. Wear structural firefighting gear.
<b>Flash Point:</b>	>300 °F
<b>Autoignition Temp:</b>	Not applicable

### Section 6 – Accidental Release Measures

---

<b>General:</b>	Spills should be contained, soaked up with absorbent material, and placed in suitable containers for disposal at a licensed facility.
<b>Waste Disposal:</b>	Incinerate or bury in a licensed facility. Do not discharge into waterways or sewer systems without proper authority.

### Section 7 – Handling and Storage

---

<b>General:</b>	Avoid breathing mist or vapors and repeated or prolonged exposure with skin. Avoid eye contact. Do not drink.
<b>Storage:</b>	Store and use in well-ventilated area between 70-80F. Avoid excessive temperatures, low or high. Avoid moisture.

### Section 8 – Exposure Controls & Personal Protection

---

<b>Clothing:</b>	Gloves, coveralls, apron, boots as necessary to prevent skin contact.
<b>Eyes:</b>	Chemical goggles; also wear face shield if splashing hazard exists.
<b>Respiration:</b>	Approved organic vapor mist respirator unless adequate local exhaust ventilation is provided, or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators.
<b>Ventilation:</b>	Use local exhaust to control vapors/mists.

## SAFETY DATA SHEET

---

### Section 9 – Physical & Chemical Properties

---

<b>Color:</b>	Translucent Pink
<b>Form:</b>	Liquid
<b>Odor:</b>	Slight
<b>Odor Intensity:</b>	Mild
<b>Specific Gravity:</b>	.96
<b>Boiling Point</b>	>65 C
<b>Solubility:</b>	None

---

### Section 10 – Stability & Reactivity

---

<b>Stability:</b>	Stable
<b>Conditions to Avoid:</b>	None
<b>Incompatibility:</b>	Oxidizing material can cause a reaction. Water, moisture, or humid air can cause hazardous vapors to form.
<b>Hazardous Decomposition:</b>	Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Carbon oxides and traces of incompletely burned carbon compounds, silicon dioxide, formaldehyde, metal oxides.

---

### Section 11 – Toxicological Information

---

No applicable data for this section

---

### Section 12 – Ecological Information (Non Mandatory)

---

No applicable data for this section

---

### Section 13 – Disposal Information (Non Mandatory)

---

<b>Waste Disposal:</b>	Incinerate or bury in a licensed facility. Do not discharge into waterways or sewer systems without proper authority.
<b>Container Disposal:</b>	Steel drums must be emptied (as defined by RCRA, Section 261.7 or state regulations that may be more stringent) and can be sent to a licensed drum reconditioner for reuse, a scrap metal dealer, or an approved landfill. Drums destined for a scrap dealer or landfill must be punctured or crushed to prevent reuse.

---

### Section 14 – Transportation Information (Non Mandatory)

---

Not regulated by the Department of Transportation



## SAFETY DATA SHEET

---

### Section 15 – Regulatory Information (Non Mandatory)

---

No data available

**Hazardous Health Rating:** Health: 3 Fire: 3 Reactivity: 1

---

### Section 16 – Other Information

---

No data available

---

The information contained in this Safety Data Sheet is to the best of Alumilite's knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. **NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE CONCERNING THE INFORMATION HEREIN PROVIDED OR ANY RELATED PRODUCT.** User is responsible for determining whether the Alumilite product is fit for user's particular purpose and suitable for user's use or application. Given the variety of factors that can affect the use and application of an Alumilite product, it is the user's obligation to determine the suitability of the product for its intended application, and user assumes all risk and liability for safe use of the product. Alumilite's liability is limited to product replacement only after review/testing of product alleged to be defective that is returned to Alumilite in accordance with Alumilite's Shipping and Returns Policy. In no event shall Alumilite be liable for punitive, consequential or indirect damages or damages in excess of the purchase price of the product.

---

**Revised May 2, 2018**